


BF200 da 1 a 5 leve


Caratteristiche generali / Technical characteristics		
	l/min	GPM
• Portata nominale / Nominal flow	17	4,5
• Portata limite / Max flow	25	6,6
	bar	PSI
• Pressione nominale / Nominal pressure	250	3600
• Pressione max sugli utilizzi / Max pressure on ports	320	4700
• Contropressione max allo scarico / Max pressure in tank-line	80	1100

BF200 from 1 to 5 levers



BF201/...=	n° 1 elemento prioritario n° 1 priority element
BF202/...=	n° 2 elementi prioritari n° 2 priority elements
BF203/...=	n° 3 elementi prioritari n° 3 priority elements
BF204/...=	n° 4 elementi prioritari n° 4 priority elements
BF205/...=	n° 5 elementi prioritari n° 5 priority elements

MOD	L	I	Kg
BF20.../1	106	80	2,4
BF20.../2	136	110	3,2
BF20.../3	166	140	4,0
BF20.../4	196	170	4,8
BF20.../5	226	200	5,6



FILETTATURA STANDARD - STANDARD THREADS							
COD	A-B	P	T	P ₂	T ₂	P ₃	T ₃
G	1/4"	1/4"	3/8"	3/8"	3/8"	1/4"	1/4"
F	9/16" - 18	9/16" - 18	3/4" - 16	3/4" - 16	3/4" - 16		

◀ Su richiesta filettature diverse
 Other threads available on request

